

**PAINT INDUSTRIES PTY LTD**

61 Lionel Street NAVAL BASE WA 6165 Telephone: (08 )9437 1488 Fax: (08) 9410 2395

EMERGENCY Telephone No: (08) 9341 8771

**Material Safety Data Sheet**

DATE OF ISSUE 31/01/2009

**Classified as Hazardous according to criteria of Worksafe Australia**

R10 Flammable.  
 R20/21 Harmful by inhalation and in contact with skin.  
 R38 Irritating to skin.  
 S16 Keep away from sources of ignition - no smoking.  
 S24 Avoid contact with skin.

**IDENTIFICATION**

Product Name: **TOP DEK ALUMINIUM BRIGHT SILVER SILVER PAINT**  
 Other Names:  
 Manufacturer's Product Code: **6001**  
 UN Number: **1263**  
 Dangerous Goods Class & Subsidiary Risk: **3.2**  
 Hazchem Code: **3(Y)E**  
 Poisons Schedule Number: **N/A**  
 Use: **AS A METAL ROOF PAINT, EQUIPMENT FINISHING OR GENERAL PURPOSE SILVER PAINT COATING.**

N/A' = Not Allocated

**Physical Description/Properties**

Appearance: **Bright Silver**  
 Boiling Point/Melting Point: **116 deg C.**  
 Vapour Pressure: **7.0mm Hg @ 25 deg C.**  
 Specific Gravity: **0.97 kg/l**  
 Flashpoint: **32 deg C.**  
 Flammability Limits: **Flammable**  
 Solubility in Water: **N/A**

**Other Properties:**

Percentage Volatiles **54.4**

**Ingredients**

Chemical Name:	CAS Number:	Proportion:
<b>Aluminium Paste</b>	<b>7429-90-5</b>	<b>(Med 10-60%)</b>
	<b>8052-41-3</b>	<b>(Low &lt;10%)</b>
<b>Aromatic Hydrocarbon Resin</b>		<b>(Med 10-60%)</b>
<b>Polymerised Oil</b>	<b>67746-0801</b>	<b>(Med 10-60%)</b>
<b>Hydrocarbon Solvent</b>	<b>64742-88-7</b>	<b>(Med 10-60%)</b>

**HEALTH HAZARD INFORMATION****Health Effects:**

*Acute:*  
 Swallowed: **Irritating. Will affect digestive tract when swallowed in volume**  
 Eye: **Slightly irritating. May affect eyes with prolonged exposure.**  
 Skin: **Slightly irritating. May affect skin on prolonged contact.**  
 Inhaled: **Harmful. May cause headache & dizziness. Vapour may cause irritation to mucous membranes & respiratory tract.**

*Chronic:***First Aid**

Swallowed: **If swallowed contact a Doctor or Poisons Information service. Do not induce vomiting. Give water to drink & seek medical advice.**  
 Eye: **Gently flush with running water, holding eyelids opened for 15mins. Seek medical attention.**  
 Skin: **Remove contaminated clothing & gently flush affected areas with soap & water. Seek medical attention if irritation develops. Laundry clothing before re-use.**

**PAINT INDUSTRIES PTY LTD**  
**61 Lionel Street NAVAL BASE WA 6165 Telephone: (08 )9437 1488 Fax: (08) 9410 2395**  
**EMERGENCY Telephone No: (08) 9341 8771**

## Material Safety Data Sheet

**Classified as Hazardous according to criteria of Worksafe Australia**

Inhaled: **Remove patient from exposure, into fresh air. Apply artificial respiration if patient has stopped breathing. Seek medical attention. Treat Symptomatically**

**Advice to Doctor**

### **PRECAUTIONS FOR USE**

Exposure Standards: **Recommend 80ppm 8 hour time weighted average for hydrocarbon solvent.**

Engineering Controls: **In confined, poorly ventilated areas, use mechanical extraction ventilation. (explosion proof)**

Personal Protection: **Overalls, goggles, PVC gloves and organic vapour respirator.**

Flammability: **Flammable liquid. Vapour may form explosive mixtures with air. Vapour may ignite on pumping or pouring due to static electricity. Keep away from sources of ignition. Do not smoke.**

### **SAFE HANDLING INFORMATION**

Storage and Transport: **Keep containers tightlled sealed. Keep away from sources of ignition. Keep out of reach of children.**

Spills and Disposal **Do not allow large spills to enter drains or sewers. Inform Police if this occurs. Absorb spilt product onto sand or earth & dispose to land fill. Wear PVC gloves, goggles and suitable respirator. Keep sources of ignition away.**

Fire/Explosion Hazard: **Call fire brigade. Keep this MSDS handy. Use vapouring liquid, dry chemical, carbon dioxide, or alcohol foam extinguisher. Prevent runoff from entering drains.**

### **OTHER INFORMATION:**

### **CONTACT POINT:**

**Manager - (08) 9437 1488**