

PAINT INDUSTRIES PTY LTD
 61 Lionel Street NAVAL BASE WA 6165 Telephone: (08)9437 1488 Fax: (08) 9410 2395
 EMERGENCY Telephone No: (08) 9341 8771

Material Safety Data Sheet

Date of Issue : 31/01/2009

Not Classified as Hazardous according to criteria of Worksafe Australia

IDENTIFICATION

Product Name:	N/A
Other Names:	TOPDEK AQUAPAVE WHITE & ALL COLOURS
Manufacturer's Product Code:	0062/ & All colours
UN Number:	N/A
Dangerous Goods Class & Subsidiary Risk:	N/A
Hazchem Code:	N/A
Poisons Schedule Number:	N/A
Use:	

Physical Description/Properties

Appearance:	White Liquid
Boiling Point/Melting Point:	100 deg C.
Vapour Pressure:	17.5 (water) mm Hg @ 25 deg C.
Specific Gravity:	1.40 kg/l
Flashpoint:	N/A deg. C.
Flammability Limits:	N/A
Solubility in Water:	N/A

Other Properties:

Percentage Volatiles	40
----------------------	----

Ingredients

Chemical Name:	CAS Number:	Proportion:
Acrylic Emulsion		(Med 10-60%)
Barium Sulphate		(Low <10%)
Extender	1317-65-3	(Low <10%)
Propylene Glycol		(Low <10%)
Titanium Dioxide/Colour Pigments	13463-67-7	(Med 10-60%)

HEALTH HAZARD INFORMATION

Health Effects:

Acute:

Swallowed:	Slightly irritating. May affect digestive tract when swallowed in volume.
Eye:	Slightly irritating. May affect eyes with prolonged exposure.
Skin:	Slightly irritating. May affect skin on prolonged contact.
Inhaled:	Slightly irritating. May cause nausea on prolonged contact.

Chronic:

First Aid

Swallowed:	Contact a Dr. or Poisons Information Service. Do not induce vomiting. Give water to drink and seek medical attention.
Eye:	Gently flush with running water, holding eyelids open, for 15 minutes.
Skin:	Wash affected area immediately with soap and water.
Inhaled:	The vapour may be an irritant to the mucous membranes and respiratory tract.

First Aid Facilities:

Advice to Doctor:

Treat symptomatically.

PAINT INDUSTRIES PTY LTD
61 Lionel Street NAVAL BASE WA 6165 Telephone: (08)9437 1488 Fax: (08) 9410 2395
EMERGENCY Telephone No: (08) 9341 8771

Material Safety Data Sheet

Not Classified as Hazardous according to criteria of Worksafe Australia

PRECAUTIONS FOR USE

Exposure Standards:	Not applicable
Engineering Controls:	In confined, poorly ventilated aears, use mechanical extraction ventilation.
Personal Protection:	Normal site protection plus overalls and safety glasses. Observe good industrial hygiene.
Flammability:	Not applicable.

SAFE HANDLING INFORMATION

Storage and Transport:	Store in a cool, dry place; out of reach of children.
Spills and Disposal	Do not allow large spills to enter drains or sewers. Inform police if this occurs. Absorb spilt product onto sand or earth.
Fire/Explosion Hazard:	Not applicable.

OTHER INFORMATION:

CONTACT POINT:

Manager (09) 9437 1488

==

