

PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE
(09) 437 1488
FAX: (09) 410 2395

61 Lionel Street
Naval Base 6165
WESTERN AUSTRALIA

P.O. BOX 83
North Fremantle 6159
WESTERN AUSTRALIA

MADE IN WA
GUARANTEED QUALITY
DATE: 31/01/2009

PRODUCT BULLETIN

F.C. 303

BRIGHT SILVER 6001

Description: An extremely bright solvent based aluminium paint for general purpose exterior & interior application.

Properties: Bright reflective colour reduces heat transfer. Heat resistant to 200°C. Useful also as a stain sealer where normal sealers fail.

Uses: Metal objects, wrought iron, roofs, storage tanks, sheds, silos, structural steel areas & metal areas where a degree of heat resistance up to 200°C is required. Can be applied to other substrates after proper preparation.

Surface Preparation: All surfaces should be clean and free from oil, grease and other contaminants. Rust, mill scale and loose paint should be removed, by mechanical means or sand blasted where necessary and a coat of TOP DEK RED OXIDE ZINC PHOSPHATE PRIMER applied. Other surfaces should be prepared according to the substrate requirement.

Thinning: Use straight from can. May be thinned, if necessary, with mineral turps.

Application: Brush, roller or spray – usually two coats.

Spread Rate: Approx. 15m² per litre.

Drying Time: At 25°C touch dry 4-6 hours; recoat after 16 hours.

Clean-Up: Clean all equipment immediately with mineral turps.

Standard Packaging: 20L 4L 1L. 500 ml 250 ml

Colours: Bright Silver.