

# PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street  
Naval Base 6165  
WESTERN AUSTRALIA

P.O. BOX 83  
North Fremantle 6159  
WESTERN AUSTRALIA

MADE IN WA  
GUARANTEED QUALITY  
DATE: 31/01/2009

---

## PRODUCT BULLETIN

## F.C. 305

---

### AQUAPAVE.

**Description:** New technology, water based, acrylic paving paint.

**Properties:** Extremely durable, low sheen paving paint which can be applied to most paving surfaces without a primer or undercoat.

**Uses:** Interior or exterior application to garage floors, driveways, car ports, patios, pool surrounds, verandahs etc. Non Skid Additive can be added to give a non skid finish.

**Surface Preparation:** All surfaces should be clean and free from grease & oil, loose or flaking paint, salt residue and any other contaminants. Oil & grease should be removed with a strong detergent wash & high pressure water blast & then rinsed with clean water.

**Previously Painted Surfaces:** Must be sand papered with 40-60 grit sand paper. Bare concrete surfaces should be acid etched with a solution of 1 part hydrochloric acid & 7 parts water and then hosed off with clean water. All surfaces should be dry for application of Aquapave.

**Thinning:** 10% with water on bare concrete only. Thinning is not required. Apply as supplied.

**Application:** Thoroughly mix with a broad flat paddle and apply two coats by brush or short nap roller allowing a minimum of 2 hours between coats.

**Spread Rate:** Approx. 10m<sup>2</sup> -12m<sup>2</sup> per litre per litre.

**Drying Time:** At 25°C and low humidity Aquapave may be walked on after 2 hours and subjected to light vehicle traffic after 24 hours. Full cure to maximum hardness will take at least 7 days, before parking on. Variations in weather conditions will affect drying time.

**Clean-Up:** Wash brushes & rollers in water immediately after use. Remove spills & spots with a damp cloth.

**Standard Packaging:** 4L & 1L.

# PAINT INDUSTRIES PTY LTD

2

---

## PRODUCT BULLETIN

---

**F.C. 305**

**Colours:**

White 0062 (can be tinted)  
Cable Beach Sand 3008  
Flint Grey 1023  
Black 1024

Kakadu Brown 2016  
Kimberley Red 2022  
Stirling Green 4014

**Warning** (1) Whilst Aquapave is slip resistant care should be taken in wet or oily conditions.  
(2) Damage to Aquapave can be caused by hot tyres resting on the surface.

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.