

# PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street  
Naval Base 6165  
WESTERN AUSTRALIA

P.O. BOX 83  
North Fremantle 6159  
WESTERN AUSTRALIA

MADE IN WA  
GUARANTEED QUALITY  
DATE: 31/01/2009

---

## PRODUCT BULLETIN

F.C. 310

---

### ACRYLIC LOW SHEEN 0136

**Description:** A low odour, hard wearing, fully washable paint with inbuilt stain resistant qualities for internal broadwall areas and semi-exposed external surfaces.

**Properties:** High opacity and covering power combined with new low odour, stain resistant technology makes this product easy and pleasant to use. Based on 100% acrylic resin for excellent durability as well as superior washability. Dries to a very pleasant low sheen finish.

**Uses:** Particularly suited for use on walls of living rooms, family rooms, children's rooms and hallways, where stain resistance and washability is required.

**Surface Preparation:** Allow new plaster to cure for 8 weeks and new cement render for 4 weeks. All surfaces must be thoroughly cleaned, dry and free of all loose dirt, dust, grease, mould, loose & flaking paint & loose surface plaster. Efflorescence or mould must be treated with the appropriate sterilising wash. To provide a key for better adhesion, lightly sandpaper gloss or semi gloss finishes and wipe clean.

**Previously Painted Surfaces:** Should be washed down with sugar soap as directed and where severe chalking is present apply a binding sealer.

Fill all cracks and holes and surface damage with suitable filler and sandpaper smooth. Spot seal these areas with TOP DEK ACRYLIC SEALER UNDERCOAT.

Plaster Glass must be sealed with TOP DEK SUPASEAL.  
Gyprock or similar paper faced boards should be sealed with TOP DEK GYPSEAL.

For best results, unpainted plaster, fibro, cement render, brick & masonry should be given one coat of TOP DEK ACRYLIC SEALER UNDERCOAT.

**Thinning:** For conventional or airless spray only, thin up to 10% with water. Otherwise use directly from the can as supplied, for brush or roller application.

**Application:** Brush, roller or spray. Apply two full & even coats allowing a minimum of two hours between coats. When rolling use a medium nap (10mm) pure wool or synthetic roller. On rough surfaces use a longer nap roller according to the roughness of the surface and texture of finish desired.

**Spread Rate:** Up to 16 m<sup>2</sup> per litre depending on porosity of surface.

**Drying Time:** At 25°C, touch dry in 30 minutes. Recoat after a minimum of two hours. In cold or damp conditions allow longer times. Do not use when temperature is, or may fall below, 10°C.

**Clean-Up:** Clean all equipment immediately after use with water.

**Standard Packaging:** 10L 4L 1L.

**Colour:** Stain resistant white and tint bases for colour reproduction.

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.