

PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street
Naval Base 6165
WESTERN AUSTRALIA

P.O. BOX 83
North Fremantle 6159
WESTERN AUSTRALIA

MADE IN WA
GUARANTEED QUALITY
DATE: 31/01/2009

PRODUCT BULLETIN

F.C. 313

CEILING FLAT

0021

Description: A premium quality interior, extremely flat, water based acrylic paint especially formulated for ceilings..

Properties: High opacity with easy application. An extremely flat finish which helps to hide plastering imperfections.

Uses: Specially formulated for ceilings. Can be used on all ceiling substrates e.g. plaster, gyprock, fibro cement and plaster glass. (See "SURFACE PREPARATION" re plaster glass).

Surface Preparation: Allow new plaster to cure for 8 weeks.
All surfaces must be thoroughly cleaned, dry and free of all loose dirt, dust, grease, mould, loose or flaking paint and loose surface plaster. Efflorescence or mould must be treated with the appropriate sterilising wash. To provide a key, all gloss or semi gloss finishes should be lightly sand-papered and wiped clean.

Previously Painted Surfaces: Should be washed down with sugar soap as directed and where severe chalking is present apply a binding sealer.
Fill all cracks, holes & surface damage with suitable filler and sandpaper smooth.
Spot seal these areas with appropriate sealer.

Plaster Glass must be sealed with TOP DEK SUPASEAL.
Gyprock or similar paper faced boards should be sealed with TOP DEK GYPSEAL.

For best results, unpainted plaster or fibro, should be given one coat of TOP DEK ACRYLIC SEALER UNDERCOAT.

Thinning: For conventional or airless spray only, thin up to 10% with water. Otherwise use direct from the can as supplied.

Application: Brush, roller or spray. Apply one or two coats as required allowing a minimum of two hours between coats. When rolling use a short to medium nap (max 10mm) pure wool or synthetic roller.

Spread Rate: Approximately 16 m² per litre, depending on porosity of surface.

Drying Time: At 25°C, touch dry in 20-30 minutes. Recoat after a minimum of 2 hours. In cold or damp conditions allow longer times. Do not apply when temperature is, or may, fall below 10°C.

Clean-Up: Clean all equipment immediately after use with water.

Standard Packaging: 10L 4L 2L 1L

Colour: White.

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.