PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE
(08) 9437 1488
FAX: (08) 9410 2395

61 Lionel Street
Naval Base 6165
WESTERN AUSTRALIA

P.O. BOX 83
North Fremantle 6159
WESTERN AUSTRALIA

MADE IN WA
GUARANTEED QUALITY
DATE: 31.01.2009

PRODUCT BULLETIN F.C. 327

TOPDEK LIMECOAT 0087 0088

Description: A lime rich coating offering a broken colour appearance through the "lime blooming" process.

Properties: Interior or exterior use on substrates prone to little or no movement. Water staining will occur in exposed environments enhancing the aged patina.

Uses: As a feature finish both interior and exterior.

Surface Preparation: All surfaces should be clean and free of all loose dirt, dust, grease, mould, flaking or peeling paint and loose surface plaster. Efflorescence or mould must be treated with the appropriate sterilising wash.

All surfaces to be coated should be of even porosity to eliminate colour shadowing. Timber should be undercoated with two coats of TOPDEK Weathertuff Low Sheen Acrylic. Fill all holes and cracks with suitable filler and sand smooth. Spot prime these areas with the appropriate sealer. Plasterglass must be sealed with TOPDEK Supa Seal. Gyprock or paperfaced board must be sealed with TOPDEK Gypseal.

Application: Apply by broad brush direct from the can. No thinning is required. Brush on in a random pattern making sure a wet edge is maintained to create a washed appearance. Apply second coat after twelve hours depending on drying conditions. Tinted undercoat may be required for some colours.

Spread Rate: Approx 8 sq metres per litre.

Drying Time: @ 24°C and up to 50% RH – touch dry in 30 minutes. Recoat in 12 hours.

Clean Up: Wash equipment in water immediately after use. Remove spills or spots immediately with a damp cloth.

Standard Packaging: 1 lt, 4 lt.

Colour: Standard and Deep bases, all colours are tinted from these bases.

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.