

PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE
(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street
Naval Base 6165
WESTERN AUSTRALIA

P.O. BOX 83
North Fremantle 6159
WESTERN AUSTRALIA

MADE IN WA
GUARANTEED QUALITY
DATE: 21/01/2016

PRODUCT BULLETIN

F.C. 329

TOPDEK RUSTSTOP

WHITE	0017
MATT BLACK	1005
GLOSS BLACK	1006
SIGNAL RED	2038
MID YELLOW	3005
BRUNSWICK GREEN	4006
NAVY BLUE	5003
SILVER	6003
MICACEOUS IRON OXIDE	1019

Description: Topdek Ruststop is a high quality single pack modified enamel with added benefit of glass flake reinforced.

Properties: High gloss finish with excellent gloss & colour, except for Micaceous iron oxide which is a matt finish, and highly sought after for its unique decorative appearance. Easy application & wet edge retention with excellent secondary flow to provide a very smooth finish.
Long term durability under exterior & interior applications.

Uses: Topdek Ruststop may be applied directly to rust affected substrates without priming, provided directions are strictly adhered to, for interior & exterior.

Surface Preparation: All surfaces should be clean and free of all wax, oil, grease, loose rust or paint, or other contaminants. Clean thoroughly by scraping, wire brushing or sanding. Previously painted areas should be sound and free of chalking. Heavily rusted areas should be treated with a rust converter, then primed with either Topdek Zinc Phosphate Primer or Topdek Cold Galv Primer. To maximise results on new steel, should be treated with Topdek Zinc Phosphate Primer, Topdek Galv Iron Primer or Topdek Cold Galv Primer.

Thinning: Not normally required. Apply direct from can. For conventional or airless spray, thin if necessary with up to 5% min turps, or enamel thinners.

Application: Stir contents thoroughly before use. Apply directly using a good quality brush, short nap or foam roller or spray.

Spread Rate: Approx 10-14 sq mts per litre, depending on porosity of substrate.

Drying Time: Touch dry in 4-6 hours. Recoat after 24 hours. Full cure in 3-7 days – depending on atmospheric conditions. Do not apply if temperature falls below 10°C or rain is forecast.

Clean Up: Clean all spills & equipment with min turps or enamel thinners.

Standard Packaging: 500ml, 1lt & 4lt

Colour: As above, factory packaged colour.

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.