

PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street
Naval Base 6165
WESTERN AUSTRALIA

P.O. BOX 83
North Fremantle 6159
WESTERN AUSTRALIA

MADE IN WA
GUARANTEED QUALITY
DATE: 12/01/2009

PRODUCT BULLETIN

F.C. 330

SQUASH COURT PAINT WHITE 0027 & COLOURS

Description: A professional premium quality, washable hard wearing, water based paint that dries to a flat finish, to alleviate ball slip.

Properties: A quick drying, tough flat finish with a high resistance to scuff/ball marking & excellent adhesion.

Uses: Highly pigmented & especially formulated for squash court walls.

Surface Preparation: Allow new plaster to cure for 8 weeks and new cement render for 4 weeks. All surfaces must be thoroughly cleaned, dry and free of all loose dirt, dust, grease, mould, loose or flaking paint and loose surface plaster. Efflorescence or mould must be treated with the appropriate sterilising wash. To provide a key for better adhesion, lightly sandpaper gloss or semi gloss finishes and wipe clean.

Previously Painted Surfaces: Should be washed down with sugar soap as directed and where severe chalking is present apply a binding sealer. Fill all cracks, holes & surface damage with suitable filler and sandpaper smooth. Spot seal these areas with TOPDEK ACRYLIC SEALER UNDERCOAT.

Plaster Glass: **Must** be sealed with TOPDEK SUPASEAL. Gyprock or similar paper faced boards should be sealed with TOPDEK GYPSEAL.

For best results, unpainted plaster, fibro, cement render, brick & masonry should be given one coat of TOPDEK ACRYLIC SEALER UNDERCOAT.

Thinning: Not recommended, but up to 10% water (will slow drying).

Application: Brush, roller or spray. Apply two full & even coats allowing a minimum of two hours between coats. When rolling use a medium nap (10mm) pure wool or synthetic roller. On rough surfaces use a longer nap roller.

Spread Rate: Approximately 10-12 m²/lt.

Drying Time: At 25°C, normally dries in 15-20 mins, if well ventilated & may be re-coated in approx 2 hours. Can be played on next day. Humid & damp conditions may lengthen dry time.

Clean-Up: Clean all equipment immediately after use with water.

Standard Packaging: 20L only.

Colour: White or pastel colours.

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.