

PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(09) 437 1488

FAX: (09) 410 2395

61 Lionel Street
Naval Base 6165
WESTERN AUSTRALIA

P.O. BOX 83
North Fremantle 6159
WESTERN AUSTRALIA

MADE IN WA
GUARANTEED QUALITY
DATE: 31/01/2009

PRODUCT BULLETIN

P.S. 116

STRONGMAN SEALER 7018

Description: Water based clear acrylic sealer for porous surfaces.

Properties: Fast dry, penetrating, water clear.

Uses: As a clear sealer to protect and preserve limestone and cement blocks.

Surface Preparation: Remove all loose dirt and dust. On old surfaces which may be discoloured wash with a bleach solution to kill mould and hose off thoroughly with a pressure washer.

Thinning: Not usually required but may be thinned up to 10% with water to aid penetration on hard surfaces.

Application: Apply by brush, roller or spray. Two coats allowing 4 hours between coats is the preferred procedure.

Spread Rate: Approximately 10 m² per litre depending on the porosity of the surface.

Drying Time: Touch dry 20 –30 minutes. Recoat after 4 hours minimum.

Clean-Up: Clean equipment immediately after use with water. Remove spills immediately with water.

Standard Packaging: 20L

Colour: Clear only.

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.