

PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(09) 437 1488

FAX: (09) 410 2395

61 Lionel Street
Naval Base 6165
WESTERN AUSTRALIA

P.O. BOX 83
North Fremantle 6159
WESTERN AUSTRALIA

MADE IN WA
GUARANTEED QUALITY
Amended DATE: 31.10.09

PRODUCT BULLETIN

S.C.505

TUFF GRIP A.R: - 0039

Description: A water based acrylic, high build coating, which is abrasion resistant, flexible and provides a waterproof membrane film. Tuff Grip produces a very low sheen finish.

Properties: Tuff Grip is extremely flexible with an elongation factor of 300% and a recovery of 115%. It is not harmful to foodstuffs and is inert to gaseous fumigants. At recommended film thickness Tuff Grip is a very efficient waterproof membrane.

Uses: For use on masonry, concrete and galvanised iron surfaces in both interior and exterior applications. Applied as a high build coating – Tuff Grip will cover fine cracks in substrate and remains flexible so as not to crack after drying.

Tuff Grip can be used as a water proof membrane when applied in high film builds of 500um over porous surfaces.

Excellent for sport court coatings, also reduces fluff delamination of tennis balls & provides excellent grip characteristics with sport shoes.

Surface Preparation: All surfaces should be clean and free from loose or flaking paint, oil, grease and other contaminants. Mould or efflorescence should be treated with appropriate sterilizing wash. On extremely porous surfaces applying one coat of TOPDEK ACRYLIC UNDERCOAT will be of benefit.

Thinning: Thinning is not usually required. Water if necessary.

Application: Tuff Grip should be applied as a high build coating aiming for 500um dry film build. Two coats applied by brush, roller or appropriate spray should achieve the desired film thickness.

Spread Rate: Approximately 3m² per litre @ 200um D.F.T.
Approximately 1.2m² @ 500um D.F.T.

Drying Time: Will vary according to film build and atmospheric conditions, but at 25°C drying should be achieved in 4 – 6 hours. **N.B.** Do not apply at temperature below 10°C or with relative humidity above 85%.

Clean-Up: Equipment will clean up with water.

Standard Packaging: 20L

Colour: White, which can be tinted to required pastel shades.

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.