

PAINT INDUSTRIES PTY LTD
 61 Lionel Street NAVAL BASE WA 6165 Telephone: (08) 9437 1488 Fax: (08) 9410 2395
 EMERGENCY Telephone No: (08) 9341 8771

Material Safety Data Sheet

Date of Issue 31/01/2009

Not Classified as Hazardous according to criteria of Worksafe Australia

IDENTIFICATION

Product Name:	N/A
Other Names:	THERMALCOAT
Manufacturer's Product Code:	N/A
UN Number:	28
Dangerous Goods Class & Subsidiary Risk:	N/A
Hazchem Code:	N/A
Poisons Schedule Number:	N/A
Use:	As a heat re-radiating paint for use on most external surfaces- concrete, brick, timber, primed metal etc.

Physical Description/Properties

Appearance:	White Liquid
Boiling Point/Melting Point:	100 deg C.
Vapour Pressure:	17.5 (water) mm Hg @ 25 deg C.
Specific Gravity:	1.22 kg/lit
Flashpoint:	N/A
Flammability Limits:	N/A
Solubility in Water:	Yes

Other Properties:

Percentage Volatiles	51.8
----------------------	------

Ingredients

Chemical Name:	CAS Number:	Proportion:
Acrylic Copolymer		(Med 10-60%)
Propylene Glycol		(Low <10%)
Titanium Dioxide		(Med 10-60%)
Special Additives		(Low <10%)

HEALTH HAZARD INFORMATION

Health Effects:

<i>Acute:</i>	
Swallowed:	May cause irritation to mouth, throat and stomach.
Eye:	May be an eye irritant.
Skin:	Repeated or prolonged contact may lead to irritation.
Inhaled:	

Chronic:

First Aid

Swallowed:	Contact a doctor or Poisons Informaton Service. Do not induce vomiting. Give water to drink and seek medical advice.
Eye:	Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.
Skin:	Wash affected area immediately with soap and water.
Inhaled:	Water based - N/A
First Aid Facilities:	

Advice to Doctor:

Treat sytmotomically.

PAINT INDUSTRIES PTY LTD
61 Lionel Street NAVAL BASE WA 6165 Telephone: (08)9437 1488 Fax: (08) 9410 2395
EMERGENCY Telephone No: (08) 9341 8771

Material Safety Data Sheet

Not Classified as Hazardous according to criteria of Worksafe Australia

PRECAUTIONS FOR USE

Exposure Standards: N/A

Engineering Controls: In confined, poorly ventilated areas, use mechanical extraction ventilation.

Personal Protection: Normal site protection plus overalls and safety glasses. Observe good industrial hygiene.

Flammability: N/A

SAFE HANDLING INFORMATION

Storage and Transport: Store in a cool dry place. Material is non-flammable.
Spills and Disposal: Do not allow large spills to enter drains or sewers. Inform police if this occurs. Absorb spilt product onto sand or earth and dispose to land fill.

Fire/Explosion Hazard: N/A

OTHER INFORMATION:

Recommended for tinting to Light Pastel Shades only.

CONTACT POINT:

Manager (08) 9437 1488

==