

PAINT INDUSTRIES PTY LTD
 61 Lionel Street NAVAL BASE WA 6165 Telephone: (08)9437 1488 Fax: (08) 9410 2395
 EMERGENCY Telephone No: (08) 9341 8771

Material Safety Data Sheet

Date of Issue 25/8/2009

Hazardous according to criteria of Worksafe Australia

IDENTIFICATION

N/A = Not Allocated

Product Name: **MASTERPIECE DECKING OIL**
 Other Names: **N/A**
 Manufacturer's Product Code: **7088**
 UN Number: **1263**
 Dangerous Goods Class & Subsidiary Risk: **3.2**
 Hazchem Code: **3(Y)E**
 Poisons Schedule Number: **N/A**
 Use: **Used as external oil on bare timber**

Physical Description/Properties

Appearance: **Amber liquid**
 Boiling Point/Melting Point: **135 deg C**
 Vapour Pressure: **6 mm Hg @ 25 deg C**
 Specific Gravity: **0.843**
 Flashpoint: **24 deg C**
 Flammability Limits: **1.1 - 7.7%**
 Solubility in Water: **Insoluble**

Other Properties:

Percentage Volatiles **75**

Ingredients

Chemical Name:	CAS Number:	Proportion:
Oil	8001-20-5	(Med 10-60%)
Hydrocarbon Solvents	1330-20-7	(Med 10-60%)

HEALTH HAZARD INFORMATION

Health Effects:

Acute:

Swallowed: **Irritating. Will affect digestive tract when swallowed in volume.**
 Eye: **Irritating. Will affect eyes with possible long term damage.**
 Skin: **Irritating. Will affect skin on prolonged contact.**
 Inhaled: **Irritating. May cause serious long term health problems on prolonged contact.**

Chronic:

First Aid

Swallowed: **If swallowed contact a Doctor or poisons information service. Do not induce vomiting. Give water to drink and seek medical advice. Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.**

Eye: **Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.**

Skin: **Remove contaminated clothing and gently flush affected areas with soap & water. Seek medical attention if irritation develops. Launder clothing before re-use.**

Inhaled: **Remove patient from exposure, into fresh air. Apply artificial respiration if patient has stopped breathing. Seek medical attention.**

First Aid Facilities:

Advice to Doctor:

Treat Symptomatically

PAINT INDUSTRIES PTY LTD
61 Lionel Street NAVAL BASE WA 6165 Telephone: (08) 9437 1488 Fax: (08) 9410 2395
EMERGENCY Telephone No: (08) 9341 8771

Material Safety Data Sheet

Hazardous according to criteria of Worksafe Australia

PRECAUTIONS FOR USE

Exposure Standards:	TLV for hydrocarbon solvent recommended at 100 ppm.
Engineering Controls:	In confined, poorly ventilated areas, use mechanical extraction ventilation. (Explosion proof)
Personal Protection:	Overalls, goggles, PVC gloves & organic vapour respirator.
Flammability:	Flammable liquid. Vapour may form explosive mixtures with air. Vapour may ignite on pumping or pouring due to static electricity. Keep away from sources of ignition. Do not smoke.

SAFE HANDLING INFORMATION

Storage and Transport:	Keep containers tightly sealed. Keep away from sources of ignition. Keep out of reach of children.
Spills and Disposal	Do not allow large spills to enter drains or sewers. Inform Police if this occurs. Absorb spilt product onto sand or earth and dispose to land fill. Wear PVC gloves, goggles & suitable respirator. Keep sources of ignition away.
Fire/Explosion Hazard:	Call Fire Brigade. Keep this MSDS handy. Use vapourizing liquid dry chemical, carbon dioxide, or alcohol foam extinguisher. Prevent runoff from entering drains.

OTHER INFORMATION:

CONTACT POINT:

Manager (08) 9437 1488