

# PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE  
(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street  
Naval Base 6165  
WESTERN AUSTRALIA

P.O. BOX 83  
North Fremantle 6159  
WESTERN AUSTRALIA

MADE IN WA  
GUARANTEED QUALITY  
DATE: 31/01/2011

---

## PRODUCT BULLETIN

F.C. 333

---

### TOPDEK ROOF COAT 0095

**Description:** A premium quality, waterborne environmentally friendly, satin to gloss finish for the application to prepared cement roof tiles.

**Properties:** Satin to high gloss with excellent gloss and colour retention. Very durable exterior finish. Hard finish that resists chipping over properly prepared surfaces.

**Uses:** For exterior use areas such as properly prepared and sealed cement roof tiles.

**Surface Preparation:** High pressure water clean and then a seal coat of Topdek Steriseal

**Thinning :** Not usually required. Apply 2 coats direct from the can. For spray application, thin if necessary with water.

**Application:** Spray application mainly, can be brushed

**Spread Rate:** Up to 15 sqm per litre, depending on surface porosity.

**Drying Time:** @ 25 degree Celsius and 50% RH , touch dry in 20-30mins. Recoat after 4 hours.

**Clean Up:** Clean all equipment immediately after use with water.

**Standard Packaging :** 20lt only

**Colour:** Various (Tintable).

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.