

# PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street  
Naval Base 6165  
WESTERN AUSTRALIA

P.O. BOX 83  
North Fremantle 6159  
WESTERN AUSTRALIA

MADE IN WA  
GUARANTEED QUALITY  
DATE; 31/01/2009

---

## PRODUCT BULLETIN

P.S. 108

---

### GALV IRON PRIMER                      0019

**Description:**                      A water based primer for all types of galvanised metals. Does not require special metal pre-treatment.

**Properties:**                      Provides adhesion and corrosion resistance to all types of galvanised surfaces. Does not require extensive weathering of the surface prior to application.

**Uses:**                      As a first coat primer on unpainted, properly degreased galvanised metals, to improve the adhesion and performance of subsequent architectural coatings. Should not be used over obviously red rusted metals – these should be treated with TOP DEK RED OXIDE ZINC PHOSPHATE PRIMER.

**Surface Preparation:**                      Unpainted galvanised metals should be thoroughly washed with mineral turps, changing rags frequently, to remove oils & greases. If the surface is to be subjected to heavy knocks, pre-treatment with a phosphoric acid solution will assist.

**Previously Painted Surfaces:**                      Should be cleaned of all loose & flaking paint and bare areas spot primed only.

**Thinning:**                      Not required. Use direct from can.

**Application:**                      Apply one coat direct from the can by brush or roller. In marine environments (coastal areas) two coats should be applied allowing 2 hours drying between coats.

**Spread Rate:**                      Approximately 16m<sup>2</sup> per litre.

**Drying Time:**                      At 25°C, touch dry in 20-30 minutes. Recoat after a minimum of 2 hours. Do not use when temperature is or may fall below 10°C.

**Clean-Up:**                      Clean all equipment immediately after use with water.

**Standard Packaging:**                      4L    1L    500 ml.

**Colour:**                      Pale Cream.