

PAINT INDUSTRIES PTY LTD

61 Lionel Street NAVAL BASE WA 6165 Telephone: (08) 9437 1488 Fax: (08) 9410 2395

EMERGENCY Telephone No: (08) 9341 8771**Material Safety Data Sheet**

Date of Issue 31/01/2009

Not Classified as Hazardous according to criteria of Worksafe Australia**IDENTIFICATION**

N/A' = Not Applicable

Product Name: **ROOF COAT**
 Other Names: **N/A**
 Manufacturer's Product Code: **0095**
 UN Number: **N/A**
 Dangerous Goods Class & Subsidiary Risk: **N/A**
 Hazchem Code: **N/A**
 Poisons Schedule Number: **Not Applicable**
 Use: **For use as an aqueous, acrylic b coating on to properly prepared cement roof tiles, and masonry surfaces**

Physical Description/Properties

Appearance: **Coloured viscous liquid**
 Boiling Point/Melting Point: **100 deg C**
 Vapour Pressure: **17.5 (water) mm Hg @ 25 deg C.**
 Specific Gravity: **1.08 kg/l**
 Flashpoint: **N/A deg C.**
 Flammability Limits:

Other Properties:

Percentage Volatiles **61**

Ingredients

Chemical Name:	CAS Number:	Proportion:
Ethylene Glycol, Monobutyl Ether	111-76-2	(Low <10%)
100% Acrylic Emulsion	Proprietary	(High 60-100%)

HEALTH HAZARD INFORMATION**Health Effects:**

Acute:

Swallowed: **Slightly irritating. May affect digestive tract when swallowed in volume.**
 Eye: **Slightly irritating. May affect eyes with prolonged exposure.**
 Skin: **Slightly irritating. May affect skin on prolonged contact.**
 Inhaled: **Slightly irritating. May cause nausea on prolonged contact.**

*Chronic:***First Aid**

Swallowed: **If swallowed contact a Doctor or poisons information service. Do not induce vomiting. Give water to drink & seek medical advice.**
 Eye: **Gently flush with running water, holding eyelids open for 15mins. Seek medical attention.**
 Skin: **Wash affected area immediately with soap and water.**
 Inhaled: **Water based - not applicable.**

First Aid Facilities:

Advice to Doctor:**Treat Symptomatically**

Material Safety Data Sheet

Not Classified as Hazardous according to criteria of Worksafe Australia

PRECAUTIONS FOR USE

Exposure Standards:	Based on toxicity profiles for a number of acrylic emulsions, typical Oral Data is: ORAL LD50-RAT:>5000MG/KG
Engineering Controls:	In confined, poorly ventilated areas, use mechanical extraction ventilation.
Personal Protection:	Normal site protection plus overalls & safety glasses. Observe good industrial hygiene.
Flammability:	Not Applicable.

SAFE HANDLING INFORMATION

Storage and Transport:	Store in a cool, dry place; out of reach of children
Spills and Disposal	Do not allow large spills to enter drains or sewers. Inform Police if this occurs. Absorb spilt product onto sand or earth & dispose to land fill.
Fire/Explosion Hazard:	Not Applicable.

OTHER INFORMATION:

CONTACT POINT:

Manager - (08) 9437 1488