

# PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(09) 437 1488

FAX: (09) 410 2395

61 Lionel Street  
Naval Base 6165  
WESTERN AUSTRALIA

P.O. BOX 83  
North Fremantle 6159  
WESTERN AUSTRALIA

MADE IN WA  
GUARANTEED QUALITY  
DATE: 31/01/2009

---

## PRODUCT BULLETIN

## S.C.503

---

### TRAFFICABLE ELASTOMERIC - 0042

**Description:** A high build, flexible, low sheen, waterproof membrane coating which is suitable for moderate foot traffic areas.

**Properties:** Hard wearing, extremely flexible water based, waterproof.

**Uses:** As a waterproofing membrane in areas subject to light traffic.  
On masonry surfaces, fibro cement, cement slab roofs and cement render.

**Surface Preparation:** Ensure that the surface is clean and free from oil, grease and other contaminants. Previously painted surfaces should be sound and any loose or flaking paint removed. Mould or efflorescence should be treated with appropriate sterilizing wash. On extremely porous surfaces applying one coat of TOP DEK ACRYLIC SEALER UNDERCOAT will be of benefit.

**Thinning:** Not usually required but with water if necessary.

**Application:** Long nap roller or airless spray. Usually 2 coats are required to achieve required film build. For added strength & durability fibreglass may be laid into the first coat whilst still wet.

**Spread Rate:** 3 – 4m<sup>2</sup> per litre maximum to achieve high film build.

**Drying Time:** At 25°C 4 – 6 hours. Recoat overnight. Allow longer times in cold or damp conditions. Do not use if temperature is, or may fall below 10°C.

**Clean-Up:** Clean equipment and wipe up spills immediately with water.

**Standard Packaging:** 20L

**Colour:** White – can be tinted to pastel colours.