

# PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street  
Naval Base 6165  
WESTERN AUSTRALIA

P.O. BOX 83  
North Fremantle 6159  
WESTERN AUSTRALIA

MADE IN WA  
GUARANTEED QUALITY  
DATE: 31/01/2009

---

## PRODUCT BULLETIN SC 610

---

### TOPDEK GZP EPOXY 1026

**Description:** A two component, epoxy anti-corrosive primer pigmented with zinc phosphate.

**Properties:** For use on properly prepared surfaces in both new construction and as an industrial maintenance, primer for a range of anti-corrosive coating used in offshore, bridges & chemical & petro chemical industries.

**Uses:** GZP Epoxy is preferred for use with system for chemical environments, where zinc based materials can be subject to attack in both acidic & alkaline conditions.

**Surface Preparation:** Uncontaminated, rust free steel & irons.

**Application:** By brush, roller or spray.

**Spread Rate:** Approx 8m<sup>2</sup> / litre

**Drying Time:** At a surface temperature of 15°C, and 50% relative humidity.

Touch Dry: 1-2 hours  
Recoat: Minimum 24 hours  
Maximum 48 hours  
Full Cure: 7 Days  
Pot Life: 4-6 hours

(Application under 15°C, is not recommended. Protect against water contamination during initial stage – 72 hours. Times are reduced at increased temperatures or humidity).

**Clean Up:** Epoxy thinner.

**Colour:** Matt grey

**Mixing Ratio:** 3:1

Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.