

PAINT INDUSTRIES PTY LTD

61 Lionel Street NAVAL BASE WA 6165 Telephone: (08)9437 1488 Fax: (08) 9410 2395

EMERGENCY Telephone No: (08) 9341 8771

Material Safety Data Sheet

Date of Issue 31/01/2009

Not Classified as Hazardous according to criteria of Worksafe Australia**IDENTIFICATION**

Product Name: **STRONGMAN SEALER**
 Other Names: **LIMESTONE & CONCRETE BLOCK SEALER**
 Manufacturer's Product Code: **7018**
 UN Number: **N/A**
 Dangerous Goods Class & Subsidiary Risk: **N/A**
 Hazchem Code: **N/A**
 Poisons Schedule Number: **Not Applicable**
 Use: **Water based clear saler for limestone and concrete blocks.**

Physical Description/Properties

Appearance: **Milky liquid**
 Boiling Point/Melting Point: **100 deg C**
 Vapour Pressure: **17.5 (water) mm Hg @ 25 deg C.**
 Specific Gravity: **1.06 kg/l**
 Flashpoint: **N/A deg C.**
 Flammability Limits:

Other Properties:

Percentage Volatiles **57.4**

Ingredients

Chemical Name:	CAS Number:	Proportion:
Acrylic Emulsion	Proprietary	(High 60-100%)
Coalescent	25265-77-4	(Low <10%)
Water	N/A	(Low <10%)

HEALTH HAZARD INFORMATION**Health Effects:**

Acute:
 Swallowed: **Slightly irritating. May affect digestive tract when swallowed in volume.**
 Eye: **Slightly irritating. May affect eyes with prolonged exposure.**
 Skin: **Slightly irritating. May affect skin on prolonged contact.**
 Inhaled: **Slightly irritating. May cause nausea on prolonged contact.**

*Chronic:***First Aid**

Swallowed: **If swallowed contact a Doctor or poisons information service. Do not induce vomiting. Give water to drink & seek medical advice.**
 Eye: **Gently flush with running water, holding eyelids open for 15mins. Seek medical attention.**
 Skin: **Wash affected area immediately with soap and water.**
 Inhaled: **Water based - not applicable.**

First Aid Facilities:

Advice to Doctor:**Treat Symptomatically**

PAINT INDUSTRIES PTY LTD
61 Lionel Street NAVAL BASE WA 6165 Telephone: (08)9437 1488 Fax: (08) 9410 2395
EMERGENCY Telephone No: (08) 9341 8771

Material Safety Data Sheet

Not Classified as Hazardous according to criteria of Worksafe Australia

PRECAUTIONS FOR USE

Exposure Standards:	Based on toxicity profiles for a number of acrylic emulsions, typical Oral Data is: ORAL LD50-RAT:>5.0G/KG:RABBIT, DERMAL LD50:.5.0G/KG
Engineering Controls:	In confined, poorly ventilated areas, use mechanical extraction ventilation.
Personal Protection:	Normal site protection plus overalls & safety glasses. Observe good industrial hygiene.
Flammability:	Not Applicable.

SAFE HANDLING INFORMATION

Storage and Transport:	Store in a cool, dry place; out of reach of children
Spills and Disposal	Do not allow large spills to enter drains or sewers. Inform Police if this occurs. Absorb spilt product onto sand or earth & dispose to land fill.
Fire/Explosion Hazard:	Not Applicable.

OTHER INFORMATION:

CONTACT POINT:

Manager - (08) 9437 1488

All rights reserved (including those of translation into other Languages). No part of this Material Safety Data Sheet may be reproduced in any form - by photoprint, microfilm or any other means - not transmitted into a machine language without written permission from Paint Industries. Registered names, trademarks, etc used in the Material Safety Data Sheet even when not specifically marked as such, are not considered unprotected by law.

==

