

PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street
Naval Base 6165
WESTERN AUSTRALIA

P.O. BOX 83
North Fremantle 6159
WESTERN AUSTRALIA

MADE IN WA
GUARANTEED QUALITY
DATE: 31/01/2009

PRODUCT BULLETIN

T.F. 406

TIMBER & DECKING OIL

Description: A solvent based, low sheen penetrating oil for protecting and enhancing exterior timber.

Properties: Solvent/oil blend containing waxes and fungicides (based on a tung oil resin). Low sheen transparent finish with good water repellency.

Uses: Use on any bare timber surface including decks, furniture, fences, pergolas and joinery.

Surface Preparation: Allow new resinous timber eg. jarrah, pine to weather for four (4) weeks prior to coating. Previously coated timber should be sanded bare before application. All surfaces must be clean, dry and free of dirt, dust, grease, mould and loose or flaking paint. Treat any mould with a sterilising wash.

Thinning: Not necessary. Thinning will reduce product durability.

Application: Quality brush or flat pad applicator. Pay attention to all edges and ends. Apply 2 coats, wiping off excess after each coat.

Spread Rate: 8-10 sq mts per litre, depending on timber porosity.

Drying Time: At 25°C and 50% RH. Touch dry in 4-6 weeks – recoat after 24 hours.

Clean-Up: Mineral turps followed by warm soapy water.

Standard Packaging: 10L 4L 1L

Colour: Clear. May give slight amber hue to pale timbers. May be tinted ex factory.

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.