

PAINT INDUSTRIES PTY LTD

A.C.N. 008 753 839

TELEPHONE

(08) 9437 1488

FAX: (08) 9410 2395

61 Lionel Street
Naval Base 6165
WESTERN AUSTRALIA

P.O. BOX 83
North Fremantle 6159
WESTERN AUSTRALIA

MADE IN WA
GUARANTEED QUALITY
DATE: 31/01/2009

PRODUCT BULLETIN

U.C. 201

ACRYLIC SEALER UNDERCOAT 0024

Description: A water based acrylic latex emulsion pigmented undercoat/sealer for interior and exterior application. Can be recoated with conventional water or solvent based finishing coats.

Properties: Easy application, fast dry, free sanding and excellent gloss hold-out.

Uses: As a first coat sealer on porous surfaces such as plaster board, set plaster, fibro, brick and masonry interior or exterior applications. As an undercoat on interior or exterior timber surfaces when finishing in water or solvent based finishing systems.

Surface Preparation: All surfaces must be free of dirt, dust, grease, oil or other contaminants. Generally wash pre painted areas with sugar soap and fill cracks and holes with a suitable putty.

Gloss or semi gloss finishes must be sanded thoroughly to provide a key.

Thinning: Not usually necessary, but up to 10% with water if required.

Application: Usually direct from the can by brush, roller or spray as appropriate. Apply one or two coats as required allowing 4 – 6 hours & lightly sanding between coats.

Spread Rate: On new surfaces as a sealer 8 – 10m² per litre per litre should be achieved. On previously primed or painted surfaces up to 15m² can be achieved.

Drying Time: 20 minutes touch dry. Allow 4 – 6 hours prior to recoating with water based materials. Overnight drying should be allowed prior to recoating with solvent based top coats.

Clean-Up: Clean equipment with water immediately after use and wipe up spills and spots immediately with a damp cloth.

Standard Packaging: 10L 4L 2L 1L 500 ml

Colours: White

This information is drawn from data which at the time of printing is believed by Paint Industries Pty Ltd to be accurate. Information is provided in good faith and as a general guide to users of the product. All persons using the product should enquire independently as to the suitability of the product for the end use and the application requirements for such use. Paint Industries Pty Ltd has no control over conditions under which products are stored handled or used and any recommendations cannot be regarded as a legal warranty or liability.